

Technical Data Sheet



Printer Specifications


3D Printing Technology	Fused Filament Fabrication (FFF)
Build Volume	295 x 582 x 285 mm ³ (11.5 x 22.9 x 11.2 in ³)
Movement System	GT2 Belt Drive, Linear Rails X&Y, 12 mm Igus SST Rods and Polymer Bushings
Operating Temperature Range	From 5°C to 45°C (41°F to 113°F)
Maximum Travel Speed	125mm/s (Firmware Limited)
Bed Leveling System	Automatic BLTouch 32-Point Mesh
Calibration	Automatic X-Axis True Trimming, Z-Offset, Backlash Compensation
Connectivity	USB Serial and 8GB SD Card (Wi-Fi Connectivity Kit Available)
Mainboard	32-bit Archim 2.2b with Trinamic TMC2130 drivers and Xpand board
Enclosure	TAZguard Long Bed Enclosure Available for Purchase

Print Bed Surface	Magnetic Flex Bed System
Print Bed Heater	360W 24V Silicon
Maximum Print Surface Temperature	Up to 100°C (212°F)

Standard Equipped Layer Resolution	0.3mm (300 microns) to 0.9mm (900 microns)
Minimum Possible Layer Resolution	0.05 mm (0.002 in) with Nozzle Kit and Tool Head Change
XYZ Positional Resolution	X and Y axes - 0.01mm (10 microns) Z axis - 0.002mm (2 microns)

Factory Equipped Tool Head

Default Tool Head	Asteroid 285
Nozzle Diameter	1.2 mm
Filament Diameter	2.85 mm
Maximum Extrusion Rate	50.1 mm ³ /s (211 g/hr)
Nozzle Material	GammaMaster® Steel
Nozzle Temperature	Up to 290°C (554°F)
Additional Tool Heads Available - See Next Page	



Print Area

295 mm x 582 mm x 285 mm³
(11.5 x 22.9 x 11.2 in³)

Operating Footprint

850 x 1308 x 610 mm³
(33.5 x 51.5 x 23.5 in³)

Galaxy Tool Head Options

Galaxy Series Tool Heads are built to be user friendly and reliable. Quick filament loading and repeatable tension settings save time and reduce errors. Its compact design ensures quiet operation, stable print temperatures, and easy nozzle swaps—maximizing uptime and print quality.

Meteor 285 | Nickel Plated Brass | 0.5 mm

Superior TPU and flexible filament compatibility.

Meteor 175 | Nickel Plated Brass | 0.5 mm

Print a wide variety of materials and colors, with ease.

Asteroid 285 | GammaMaster® | 1.2 mm

Design, print, and iterate large 3D prints at incredible speed with this high-output Tool Head.

Twin Nebula 175 | Nickel Plated Brass | 0.5 mm

True multi-material printing with the widely available 1.75mm filament. Great for use with PVA supports or combining rigid and flexible materials.

Twin Nebula 285 | Nickel Plated Brass | 0.5 mm

True multi-material printing with 2.85mm filament for superior TPU performance. Great for use with PVA supports or combining rigid and flexible materials.



Scan the QR code
for Tool Head models



Material Compatibility

Open filament system capability PLA, TPU, ABS, PETg,
PVA, PVB, Nylon, PC,
and others below 290°C

Software

Operating System Capability Windows, Mac, GNU/Linux
Recommended Software Cura LulzBot Edition, Version 4.13 or newer
Firmware Marlin
Supported File Typesstl, .3mf, .obj, .x3d

Electrical

Power Requirements 100VAC - 240VAC
Output 24 volt DC, 500 watts, 21 amps
Power Supply 500W 24V Mean Well, Auto-Switching

Safety and Compliance

Certifications Available upon Request
Warranty Includes one-year warranty and access to technical support five days a week.
Optional one, two, or three-year extended warranties available.
Country of Origin USA - Fargo, ND

701-809-0800 | sales@LulzBot.com | LulzBot.com

LulzBot is a registered trademark of Fargo Additive Manufacturing Equipment 3D, LLC.